



## LATCHING FIBER OPTIC 2x1 SWITCH

### OVERVIEW

The *s/* series are opto-mechanical latching switches for the most demanding applications in fiber optic communication networks. The switch is available in 1x1, 2x1 and 2x2 variants and offers solid state reliability, accurate precision and fast response time. The switch mechanism is latching and has a very fast response time below 1 ms and only 0.5 dB insertion loss.

The miniature package withstands rugged environments and is well suited for direct mounting on printed circuit boards. The switch is qualified according to Telcordia GR 1221.

### FEATURES

- reliable
- 0.5 dB insertion loss
- 0.5 ms response time
- low PDL
- 60 dB crosstalk
- miniature size
- latching

### APPLICATIONS

- Protection Switching
- Reconfiguration
- WDM

### ORDERING INFORMATION

SL2x1-9n

### Contact:

Sercalo microtechnology ltd  
Landstrasse 151, 9494 Schaan  
Principality of Liechtenstein  
Tel. +423 237 57 97 Fax. +423 237 57 48  
www.sercalo.com e-mail: info@sercalo.com

### Ordering Information:




800 Village Walk #316  
Guilford, CT 06437  
Ph: 203-401-8093

Email orders to: [sales@xsoptix.com](mailto:sales@xsoptix.com)  
Fax orders to: 800-878-7282

## DESCRIPTION

The switches are powered by a voltage between 4.0-5.25 V on the supply pin. The switch state is selected with a CMOS or TTL signal on the selector pins. A high pulse during at least 2 ms on one of the selector pins toggles the switch into either cross state or bar state. At 0 V on the selector pins or at power off, the switch remains in the last selected state.

The switching mechanism offers the reliability of a solid state device; it neither wears out nor degrades over time. Even after billions of cycles the switching quality stays constant.




## TECHNICAL SPECIFICATIONS

	Unit	Min	Typ	Max
<b>Switch</b>				
Wavelength Range	nm	1240		1640
Insertion Loss	dB		0.5	0.9
Crosstalk	dB		75	60
Backreflection	dB		55	50
Polarisation Dependent Loss	dB		0.03	0.07
Repeatability <sup>1</sup>	dB			0.002
Switching Time	ms		0.5	1
Fiber Pigtail	µm		9/125/900	
Durability	cycles		no wear out	
<b>Package</b>				
Voltage	V	4	5	5.25
Logic Level High	V	2.1		
Logic Level Low	V			0.5
Power Consumption	mW		5	25
Selection Pulse Width	ms	2		
Operation Temperature	°C	-5		70
Storage Temperature	°C	-40		85
Size (L x W x H)	mm		43 x 16.5 x 9.5	

<sup>1</sup> value for constant temperature and polarisation

## PIN CONNECTIONS

- 1 5 V supply
- 2 bar state (port 2-4) 5 V, 2 ms pulse
- 3 cross state (port 2-3) 5 V, 2 ms pulse
- 4 ground 0 V



view from pin side

## ORDERING INFORMATION

- SL2x1-9n (900 µm loose tube)
- SL2x1-9B (250 µm bare fiber)

## Contact:

Sercalo microtechnology ltd  
 Landstrasse 151, 9494 Schaan  
 Principality of Liechtenstein  
 Tel. +423 237 57 97 Fax. +423 237 57 48  
 www.sercalo.com e-mail: info@sercalo.com